


ANEMOSTATS

Lite Kits & Louvers



LoPro Vision Lite

Anemostat low profile metal vision frame for 1 3/4" doors. U.L. approved. (or equal to above). 20 ga. cold rolled steel. Tight mitered corners, beveled glass stop and low profile, provide a clear tapered look. (See chart for fire rating)

Size	Exposed Glass
5" x 35"	3" x 33"
6" x 6"	4" x 4"
6" x 27"	4" x 25"
7" x 22"	5" x 20"
12" x 12"	10" x 10"
5" x 20"	4" x 19"
24" x 24"	22" x 22"
24" x 30"	22" x 28"
24" x 32"	22" x 30"
24" x 36"	22" x 34"
31" x 35"	29" x 33"
24" x 66"	22" x 64"

BFL123 Vision Lite

18 ga. cold rolled steel. For 1 3/4" doors with 5/8" glass. Easy installation with 2" sheet metal screws that pass through the door cutout, and fastens to the opposite side of the vision frame, thus eliminating the need to drill the door for thru bolts and saving installation time and labor. It also leaves the corridor side of the frame free of fasteners for added security and a cleaner, more aesthetic appearance.

Size	Free Area (sq. in.)
12" x 12"	72



AFDL Louver

Anemostat inverted Y louver non vision louver for 1 3/4" door. Tight mitered corners, no visible welds, counter sunk mounting holes and corridor side of frame free of fastener make for a clean, streamlined appearance. Uses: Anywhere air flow is required thru a door. For exterior use, high humidity or salt air application, product must be galvanized or stainless steel. Easy installation with #8 x 1" phillips screw that fastens auxiliary frame to the louver core, thru the cutout in the door, thus eliminating the need to drill holes in the door for the thru bolts. This method saves time and installation labor and leaves the corridors side of frame free of fasteners for added security, and a cleaner aesthetic appearance not fire rated.

Size	Free Area (sq. in.)
12" x 12"	72
18" x 12"	108
24" x 12"	144
24" x 24"	288



FLDL-UL Louver

Anemostat inverted split Y non vision louver U.L. approved. (or equal to above). 16 ga. cold rolled steel. Tight mitered corners and counter sunk mounting holes make for a clean appearance. Use for fire rated doors that need air flow of 40%. By drilling 1/4" holes thru the door, around the perimeter of the door cutout. Frame has countersunk mounting holes for #8 x 32 philips head steel thru bolts with a blank head on one side for flush appearance. Stainless steel operating springs assure proper action with the closing mechanism. For exterior use, high humidity or salt air application, product must be galvanized or stainless steel. (See chart for fire ratings.)

Size	Free Area (sq. in.)
12" x 12"	72
18" x 12"	108
24" x 12"	144
24" x 24"	288

Call Schuham for
Quick Turnaround
special orders.